

AMENDMENTS TO THE CLAIMS

Claim 1 (currently amended). A redetachable self-adhesive device, in the form of a structure

- a) comprising a surface which is bonded to one side of a ~~strip of~~ double-sided adhesive ~~sheet~~ strip with at least one end of the adhesive ~~sheet~~ strip projecting beyond at least one edge of said surface as a grip tab,
- b) the adhesive ~~sheet~~ strip being ~~of a kind that is~~ redetachable by pulling on the grip tab of the strip to stretch the strip in the direction of ~~the bond~~ a plane formed between the strip and the surface it is bonded to, wherein
- c) said surface, in the area immediately adjacent to said at least one end of the adhesive ~~sheet~~ strip projecting as a grip tab, has an average roughness R_a of 2-20 μm and has an average depth of roughness R_z of 2-100 μm .

Claims 2-4 (cancelled)

Claim 5 (previously presented). The device as claimed in claim 1, wherein the area having the average roughness R_a is produced together with the device by injection molding, or is produced by etching, grinding, embossing or spark erosion.

Claim 6 (cancelled)

Claim 7 (previously presented). The device as claimed in claim 1, wherein said surface has two opposite edges wherein the areas of said surface immediately adjacent to said two opposite edges of said surface have said average roughness R_a .

Claim 8 (currently amended). The device as claimed in claim 1, further comprising

spacers the heights of which are less than the thickness of the adhesive ~~sheet~~ strip.

Claim 9 (cancelled)

Claim 10 (currently amended) The device as claimed in claim 1, wherein the double-sided adhesive ~~sheet~~ strip is elastically or plastically extensible with or without a carrier in between the two sides of said double-sided adhesive ~~sheet~~ strip.

Claim 11 (currently amended). The device as claimed in claim 1, wherein the adhesion of the double-sided adhesive ~~sheet~~ strip is less than the cohesion, the adhesion largely disappears when the ~~sheet~~ strip is extended, and the ratio of peel force to tear load is at least 1:2.0, the ~~adhesive sheet double-sided~~ adhesive strip being based on thermoplastic rubber and tackifying resins.

Claim 12 (currently amended). The device as claimed in claim 1, wherein the surface side of the double-sided adhesive ~~sheet~~ strip opposite the surface side that is bonded to the surface of the device is lined with a release laminate or a release film.

Claim 13 (previously presented). The device as claimed in claim 1, wherein said device comprises a hook or latching projection ~~located on its front face, laterally or both.~~

Claims 14-16 (cancelled)

Claim 17 (cancelled). ~~The device of Claim 8, wherein said low static friction and low sliding friction surface is a low energy polymer surface.~~

Claim 18 (previously presented). The device of Claim 12, wherein said release laminate or release film is a siliconized release paper.